



NORDIC CLASSIC

Nordic Classic is an awning able to become part of each surroundings, performs well in even the most requiring conditions. Australia can be equipped with an additional function of adjusting the inclination angle of the awning. Thanks to a simple structure and solidity of workmanship it often finds application in functional architecture.



STANDARD CONSTRUCTION COLORS

RAL 9010

RAL 9006

RAL 7016



PRODUCT DIMENSIONS

- Minimal height: 2,05 m
- Max width: 7 m (in range from 6 to 7 m awnings have 3 arms)
- Projection: 1,6 m, 2,1 m, 2,6 m, 3,1 m, 3,6 m

DRIVE

- crank: 150 or 180 cm
- motor



STANDARD FABRICS (Nerli Collection)



SANDATEX®




GLUING OF FABRICS



During the production process we solely apply a hot gluing method with application of the highest quality of a PUR-based reactive glue. This is a modern technique of matching awning fabrics.

OPTIONAL




R-pitch system

Tilt angle:
5° - 50° (standard 30°)



Vario Volant


Fabrics:
Soltis 86 or Soltis 92
Serge 600
Max height: 1,6 m



Front bar with crank
for Vario Volant system

BRACKETS

WALL INSTALLATION



CEILING INSTALLATION



WALL INSTALLATION (R-pitch)



CEILING INSTALLATION (R-pitch)



